

# LUXVIEW

## FIX TECHNICAL DATA SHEET

### ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w$  from 0.9 (W/m<sup>2</sup>K)

Please consult typology, dimensions and glazing.

### ACOUSTIC INSULATION

Maximum glazing: 2.17 in [55 mm]

Maximum acoustic insulation:  $R_w$  = 44 dB

### CATEGORIES ACHIEVED AT TEST CENTER

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

Class 4

Water tightness (UNE-EN 122078):

Class E<sub>1200</sub>

Wind resistance (UNE-EN 12210):

Class C5

Reference test window 48.43 x 58.27 in [1.23 x 1.48 m.] 2 sashes.

SECTIONS	Frame 2.76 in [70 mm] Sash 3.07 in [78 mm]	EXTRUSION ALLOY 6063 T-5
PROFILE THICKNESS	Window 0.06 in [1.5 mm] Door 0.07 in [1.7 mm]	POLYAMIDE STRIP LENGTH Polyamide 6.6 reinforced with 25% fiberglass: 1.26, 1.38 in [32 to 35 mm]
MAXIMUM DIMENSIONS	90 Sq. Ft.	GASKETS EPDM triple gasket
MAXIMUM WEIGHT/SASH	352.7 lb	FOAMS Perimeter polyofelin foam in glazing rebate zone
FINISHES	Three standard Colors: Jet Black Anthracite Grey Emery Silver	AVIS TECHNIQUE CERTIFICATE DTA certification from CSTB lab Ref. 6/17 - 2363
	Custom Options Available	

### FIXED WINDOW SYSTEM DETAILS

Maximum Glazing Sq. Ft.: 90 sq. ft.

Frame Depth: 2.75"

Frame Width: 1.925" Exterior/ 1.925" Interior

Single, Double, Triple